



**Advantage
Construction
Supply, Inc.**

ADVANTAGE XTRA SLOW TRACK

ABA-601X

ANTI-SLIP ADDITIVE FOR HIGH SOLIDS FLOOR COATINGS

DESCRIPTION:

ADVANTAGE XTRA SLOW TRACK is a polymeric grit coating additive designed to prevent slippery conditions if the floor seal becomes wet or oily. ADVANTAGE XTRA SLOW TRACK can be easily mixed into both waterborne and solventborne seals, and will not settle out to the bottom.

Note: ADVANTAGE XTRA SLOW TRACK in a previously applied coating might contribute to slight foaming in a seal or finish applied over it. Subsequent coats should be applied smoothly with minimal agitation on the floor.

DIRECTIONS:

ADVANTAGE XTRA SLOW TRACK is only recommended for use in high solids coatings. Mix ADVANTAGE XTRA SLOW TRACK into the seal and stir thoroughly. For waterborne and solvent borne coatings, add 200 to 400 grams ADVANTAGE XTRA SLOW TRACK per gallon of seal. Apply a medium coat of the seal following normal application procedures (application of sealer with ADVANTAGE XTRA SLOW TRACK is restricted to roller, lambswool applicator, or mop). Apply the seal as evenly as possible. Frequent mild stirring of the sealer with ADVANTAGE XTRA SLOW TRACK is recommended during application. ADVANTAGE XTRA SLOW TRACK may rise to the surface over time.

An additional thin coat of seal without ADVANTAGE XTRA SLOW TRACK may be applied over seal with ADVANTAGE XTRA SLOW TRACK to help trap the grit in the seal and to provide easier cleaning. However, slip resistance may decrease as a result.

SPECIFICATIONS:

COLOR: White Powder

ODOR: Mild

DOSAGE (recommended):

For good slip resistance 200 grams per gallon of seal

For extra slip resistance 400 grams per gallon of seal

FLASH POINT: >530°F (ASTM D-92 COC)

VOLATILE CONTENT: Zero

SPECIFIC GRAVITY: 0.90

PACKAGE SIZES: 200 gram container (Good for 1 gallon)

rev. 6/18/04

ADVANTAGE CONSTRUCTION SUPPLY, INC. warrants this product to be of consistent quality. ADVANTAGE CONSTRUCTION SUPPLY, INC. 'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call ADVANTAGE CONSTRUCTION SUPPLY, INC. at (916) 381-9188.